

# ATFLUID MV 8



ACTION SERIES TRANSMISSIONS

## Lubricants

### Description

REPSOL ATFLUID MV 8 is a fully synthetic lubricant oil for automatic transmissions and power- assisted steering. It can also be used in Continuous Variable Transmissions (CVTs) in which the manufacturer allows the use of Automatic Transmission Fluid (ATF). High performance product which exceed most of the OEM specifications.

### Properties

- Formulated with friction stabilizers specific to the automatic transmissions of Asian light-vehicle manufacturers, enabling maximum smoothness and perfect functioning throughout the product's service life
- Both the product and the transmission itself will last longer, thanks to the excellent anti-oxidant, anti-wear and viscosity-control properties
- Its use is permitted in some CVTs when the manufacturer allows the use of an ATF
- Its protection additives make it a product that is perfectly compatible with the gaskets in modern transmissions, avoiding possible oil leaks

### Quality levels

- GM DEXRON II D / III H
- CHRYSLER ATF +3/+4
- HUYNDAI / KIA / MISTUBISHI SP-III
- TOYOTA T-IV
- HONDA Z-1
- NISSAN MATIC K
- MAZDA T-IV/ JWS 3309
- AISIN WARNER JWS 3309 (T-IV) / JWS 3324 (WS), AW-1
- FORD MERCON
- SUBARU ATF-HP / P/N K0140Y0700
- CHRYSLER ATF +3 / +4
- ALLISON C4
- SUZUKI 3317
- ZF TE ML 11B
- BMW/ MINI P/N 8322 9407 807
- AUDI / VW G 060 162
- VOITH H55.6335
- BENTLEY PY112995PA
- VOLVO 97325, 97335
- AND OTHERS

### Technical specifications

	UNIT	METHOD	VALUE
Colour		Visual	Red
Density at 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0.844
Viscosity at 100 °C	cSt	ASTM D 445	7.25
Viscosity at 40 °C	cSt	ASTM D 445	37
Viscosity at -40 °C	cP	ASTM D 2983	20000 max.
Viscosity index	-	ASTM D 2270	166
Flash point, open cup	°C	ASTM D 92	232
Pour point	°C	ASTM D 97	-45

The above mentioned characteristics are typical values and should not be considered product specifications.

A safety data file is available on request.

repsol.com  
+34 901 111 999  
lubricantes@repsol.com

Technical data sheet for Lubricant RAS304. Revision 1. May 2020.