

### Description

Repsol MXR 2T is a lubricant oil suitable for general usage in 2-stroke engines. Apt for a wide range of motorcycles, this product is mainly recommended for urban use. A clean oil protects the engine while keeping exhaust vents clean. Additionally, it supports very high temperature operating conditions prevalent during intensive usage due to city traffic. It also supports weight-bearing activities such as the carrying of passengers on a scooter or a small cylinder capacity motorcycle.

### Properties

- Increased lubricating power reduces wear, extending the engine's life span.
- Minimizes the formation of deposits, keeping the exhaust ports clean.
- Reduces spark plug sweating and prevents the piston rings from sticking.
- Suitable for lawnmowers, chainsaws and other equipment used for DIY or small-scale agriculture.

### Quality Levels

- API TB, API TC
- ISO-L-EGB
- JASO M345 FB

### Technical Specifications

	UNIT	METHOD	VALUE
Density 15 °C	g/mL	ASTM D 4052	0.88
Viscosity at 100 °C	cSt	ASTM D 445	7,7
Viscosity at 40 °C	cSt	ASTM D 445	53
Viscosity index	-	ASTM D 2270	110
Flash point, open cup	°C	ASTM D 92	146
Pour point	°C	ASTM D 97	-15
Sulphated ashes	% in weight	ASTM D 874	0.1
T.B.N.	mg KOH/g	ASTM D 2896	1.6

The above-mentioned characteristics are typical values and should not be considered product specifications.

A safety information file is available on request.

repsol.com  
+34 901 111 999  
lubricantes@repsol.com

Technical data sheet for Lubricant RAS150. Revision 1. March 2020.