

# REPSOL MXR 3 40



ACTION SERIES MOTORCYCLE

Lubricants

## Description

Repsol MXR 3 is a mineral grade lubricant oil for 4-stroke engines. It is designed as a general use oil to protect hard working, high mileage engines against wear. It is specially formulated for demanding riding conditions. Its viscosity rating allows optimal lubricity in the harshest environments and outstanding sealing effect in the combustion chamber, to maximize power output. Especially ideal for high temperature climate.

## Properties

- Ensures good lubrication in hard working conditions.
- Good performance in a wide range of temperatures.
- Formulated with enhanced dispersant and detergency effect. Helps to prevent the formation of lacquers and varnishes and to keep pistons clean.
- Provides adequate friction on clutch discs, prevents slippages and premature wears in joint engine and transmission (wet clutch) lubrication systems.

## Quality Levels

- API SG
- JASO T 903:2016 MA

## Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			40
Density 15 °C	g/mL	ASTM D 4052	0.88
Viscosity at 100 °C	cSt	ASTM D 445	14
Viscosity at 40 °C	cSt	ASTM D 445	131
Viscosity index	-	ASTM D 2270	105
Flash point, open cup	°C	ASTM D 92	272
Pour point	°C	ASTM D 97	-15
Sulphated ashes	% in weight	ASTM D 874	0.8
T.B.N.	mg KOH/g	ASTM D 2896	6.2

The above-mentioned characteristics are typical values and should not be considered product specifications.

A safety information file is available on request.

repsol.com  
+34 901 111 999  
lubricantes@repsol.com

Technical data sheet for Lubricant RAS201. Revision 1. March 2020.