

# REPSOL MXR PLATINUM



ACTION SERIES MOTORCYCLE

Lubricants

## Description

Repsol MXR Platinum is a top tier, fully synthetic lubricant oil for modern 4-stroke engines. Its synthetic components ensure extended oil life. It provides maximum protection for medium and high cylinder capacity engines with one, two, three or even four cylinders. The lubricant ensures maximum protection, while ensuring optimum clutch performance. It provides the ultimate boost, achieving immediate response from the engine.

## Properties

- Multigrade oil with excellent thermal stability thanks to its fully synthetic formula.
- Thanks to its viscometric properties, it enhances the engine's cold start performance. It also provides adequate lubrication over a wider range of temperatures.
- Outstanding output power released due to its viscosity.
- Its high detergent-dispersant level supports engine cleaning, maintains soot in suspension, and prevents piston deposit formation.
- Provides the proper friction on clutch discs, preventing slippages and premature wear in joint engine and transmission (wet clutch) lubrication systems.

## Quality levels

- API SN
- JASO T 903:2016 MA2

## Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			10W-50
Density a 15 °C	g/mL	ASTM D 4052	0.8555
Viscosity at 100 °C	cSt	ASTM D 445	18,62
Viscosity at 40 °C	cSt	ASTM D 445	127
Viscosity at -25 °C	cP	ASTM D 5293	7000 max.
Viscosity index	-	ASTM D 2270	168
Flash point, open cup	°C	ASTM D 92	235
Pour point	°C	ASTM D 97	-30
T.B.N.	mg KOH/g	ASTM D 2896	8.1
Sulphated ashes	% in weight	ASTM D 874	1.0
Bosch Injector Shearing:			
Viscosity at 100 °C after shear	cSt	CEC-L014-93	16,3 min.

The above mentioned characteristics are typical values and should not be considered product specifications.

A safety information file is available on request.

repsol.com  
+34 901 111 999  
lubricantes@repsol.com

Technical data sheet for Lubricant RAS204. Revision 1. January 2021.