

# REPSOL GXR GREEN 0W20



ACTION SERIES AUTOMOTIVE

## Lubricants

### Description

Repsol GXR GREEN 0W20 is a fully synthetic lubricant oil with API SN-RC and ILSAC GF-5 quality levels. A high-performance product designed to offer the best protection for engines yet does not compromise on efficiency. Good for start-stop driving, especially in urban areas. The Green series is a cost effective, fuel economical, high quality oil which meets and exceeds American and Asian lubricant quality standards.

### Properties

- Complies with stringent API SN quality requirements for modern engines that require greater protection against high temperatures.
- Low viscosity property enhances cold start performance.
- Excellent oxidation stability reduces engine deposits and build-up of sludge and harmful deposits produced in the hottest zones of the engine.
- Protects engine parts from rust and wear, leading to longer engine life.
- High viscosity index ensures good performance at elevated temperatures.

### Formal Approvals

- API SN
- ILSAC GF-5

### Technical Specifications

	UNIT	METHOD	VALUE
SAE GRADE			0W-20
Density at 15 °C	g/mL	ASTM D 4052	0.844
Viscosity at 100 °C	cSt	ASTM D 445	8.2
Viscosity at 40 °C	cSt	ASTM D 445	43
Viscosity at -30 °C	cP	ASTM D 5293	
Viscosity at -35 °C	cP	ASTM D 5293	6200 max.
Viscosity index	-	ASTM D 2270	164
Flash point, open cup	°C	ASTM D 92	230
Pour point	°C	ASTM D 97	-39
T. B. N.	mg KOH/g	ASTM D 2896	7,8
Noack Volatility	% wt	DIN 51581	15 max.

The above-mentioned characteristics are typical values and should not be considered product specifications.

A safety information file is available on request.

repsol.com  
+34 901 111 999  
lubricantes@repsol.com

Technical data sheet for Lubricant RAS007. Revision 1. March 2020.