

### Description

Repsol MXR 7 is a top tier multigrade lubricant oil suitable for modern 4-stroke engines. Its carefully selected additives offer ultimate performance, giving this product a competitive edge over similarly specced products. The lubricant has excellent wear protection for medium to high cylinder capacity engines. It also ensures proper lubrication for all other components while simultaneously maintaining optimal frictional properties for oil wet clutches.

### Properties

- Viscosimetric properties have been specially designed to lubricate large cylinder engines, running hot at high rpm.
- Efficient detergent and dispersant power ensures high levels of cleanliness are maintained in different parts of the engine.
- Provides good friction on clutch discs, preventing slippages and premature wear in joint engine and transmission (wet clutch) lubrication systems.

### Quality Levels

- API SN
- JASO T 903:2016 MA2

### Technical Specifications

	UNIT	METHOD	VALUE		
SAE Grade			10W-40	15W-40	15W-50
Density at 15 °C	g/mL	ASTM D 4052	0.866	0.821	0.870
Viscosity at 100 °C	cSt	ASTM D 445	14.3	14.45	15.53
Viscosity at 40 °C	cSt	ASTM D 445	90	100	119
Viscosity at -25 °C	cP	ASTM D 5293	7000 max.	-	
Viscosity at -20 °C	cP	ASTM D 5293	-	7000 max	7000 max
Viscosity index	-	ASTM D 2270	148	160	140
Flash point, open cup	°C	ASTM D 92	224	230	230
Pour point	°C	ASTM D 97	-27	-24	-27
T.B.N.	mg KOH/g	ASTM D 2896	7.7	7.7	7,7
Sulphated ashes	% in weight	ASTM D 874	0.7	0.7	0,7
Noak Volatility	% in weight	ASTM D 5800	12	11,3	11

*The above mentioned characteristics are typical values and should not be considered product specifications.*

A safety information file is available on request.

repsol.com  
+34 901 111 999  
lubricantes@repsol.com

Technical data sheet for Lubricant RAS203. Revision 1. March 2020.