

# REPSOL RIDER MATIC MB 4T 10W-30

Moto

## Description

Four strokes engine lubricant developed to meet the requirements of the most relevant motorcycle manufacturers. Especially recommended for scooters with dry clutch automatic transmissions. Its friction modifier additive allows the product to attain the requirements of JASO MB. Its formulation with low friction capability helps to reduce fuel consumption and optimize the power output of the engine

## Properties

- Superior protection for engine against wear and deposit formation.
- Strong durability, cleanliness and thermal reliability, improving the engine's life.
- Outstanding low friction performance which helps to increase fuel efficiency.
- Reduces the deposits on the spark plug and prevents the piston rings from sticking.

## Quality levels, approvals and recommendations

- JASO T903:2016: MB
- API SL

## Technical specifications

	UNIT	METHOD	VALUE
SAE grade			10W-30
Density at 15°C	g/cm <sup>3</sup>	ASTM D 4052	0,876
Viscosity at 100°C	cSt	ASTM D 445	11,1
Viscosity at 40°C	cSt	ASTM D 445	75
Viscosity Index		ASTM D 2270	141
Flash Point	°C	ASTM D 92	200
Pour Point	°C	ASTM D 97	-15
TBN	mg KOH/g	ASTM D 2896	5,7

*The above-mentioned characteristics are typical values and should not be considered product specifications*