

### Description

Repsol MS Gear is a lubricant specially developed for automatic transmission motorcycles. Formulated to get a smooth ride with minimal frictional loss, ensuring optimum scooter acceleration and power output. This gear lubricant provides excellent protection against wear and pitting, ensuring the proper lubrication in the transmission.

### Properties

- Superior protection against wear and deposit formation
- Shear stable feature enables the oil to reach longer drain intervals while keeping the right viscosity throughout
- Outstanding friction performance to provide the right acceleration during throttling
- Proper viscosity to lubricate the transmission and for cooling purpose, thereby preventing overheating situations

### Quality Levels

- JASO T903:2016: MA2
- API SL

### Technical Specifications

|                       | UNIT     | METHOD      | VALUE     |
|-----------------------|----------|-------------|-----------|
| SAE GRADE             |          |             | 10W-30    |
| Density at 15 °C      | g/mL     | ASTM D 4052 | 0.852     |
| Viscosity at 100 °C   | cSt      | ASTM D 445  | 11,1      |
| Viscosity at 40 °C    | cSt      | ASTM D 445  | 75        |
| Viscosity at -25 °C   | cP       | ASTM D 5293 | 7000 max. |
| Viscosity index       | -        | ASTM D 2270 | 141       |
| Flash point, open cup | °C       | ASTM D 92   | 220       |
| Pour point            | °C       | ASTM D 97   | -15 max.  |
| T. B. N.              | mg KOH/g | ASTM D 2896 | 6,0       |

*The above-mentioned characteristics are typical values and should not be considered product specifications.*

A safety information file is available on request.

repsol.com  
+34 901 111 999  
lubricantes@repsol.com

Technical data sheet for Lubricant RAS202. Revision 1. March 2020.