



NXR 3 SAE 40

Description

NXR 3 is a versatile, multi-grade lubricant oil formulated with hydrotreated GII base stocks to ensure the performance in inboard diesel engines especially adapted for marine applications for fast-running engines used in marine and leisure sectors. It is most suitable for aspirated or supercharged petrol and diesel engines. This product has been tested in harsh environments and is proven to keep engines clean and protected in different conditions. Outstanding detergent, dispersant and anti-wear properties keep the engine clean and enable effective control of soot, sludge and piston deposits.

Properties

- High detergent-dispersant level supports engine cleaning, maintains soot in suspension, and avoids deposits on piston rings.
- Multi-grade property enhances cold-start performance over a wide range of temperatures.
- Protects engine from corrosion thanks to its carefully selected additives.
- Excellent anti-wear property that aids in minimizing friction.
- Reduces lubricant consumption.

Quality levels, approvals and recommendations

- API CF/SF

	UNIT	METHOD	VALUE
SAE Grade			40
Density at 15°C	g/mL	ASTM D 4052	0.903
Viscosity at 100°C	cSt	ASTM D 445	14.9
Viscosity at 40°C	cSt	ASTM D 445	148
Viscosity Index	-	ASTM D 2270	100
Flash point, open cup	°C	ASTM D 92	>225
Pour point	°C	ASTM D 97	-21
TBN	mg KOH/g	ASTM D 2896	9
Sulphated ashes	% in weight	ASTM D 874	1.5

The above mentioned characteristics are typical values and should not be considered product specifications.