

# REPSOL GXR GREEN 5W30



ACTION SERIES AUTOMOTIVE

## Lubricants

### Description

Repsol GXR GREEN 5W30 is a multi-grade semi-synthetic lubricant which, due to its advanced set of additives, is widely recommended for use in modern passenger car engines. Its balanced and robust formulation meets and exceeds the API SN standards, protecting the engine against wear and rust. Due to its high TBN level, it can be used with high Sulphur fuels, neutralizing the acids in the combustion chamber. It provides good cold start performance and also protects the engine even in the harshest environment. The Green series is a cost effective, fuel economical, high quality oil which meets and exceeds American and Asian lubricant quality standards.

### Properties

- Additive technology developed to deal with petrol of high Sulphur content.
- Excellent antioxidant capacity to extend the lubricant life.
- Excellent viscosity rating when cold starting; lubricant pumps easily on ignition, which reduces the time necessary for the film to form, thus decreasing wear
- Outstanding cleanliness performance in the engine

### Quality Levels

- API SN
- ILSAC GF-6a

### Technical specifications

	UNIT	METHOD	VALUE
SAE GRADE			5W-30
Density at 15 °C	g/mL	ASTM D 4052	0.858
Viscosity at 100 °C	cSt	ASTM D 445	10,5
Viscosity at 40 °C	cSt	ASTM D 445	62
Viscosity at -25 °C	cP	ASTM D 5293	
Viscosity at -30 °C	cP	ASTM D 5293	6600 max.
Viscosity index	-	ASTM D 2270	158
Flash point, open cup	°C	ASTM D 92	220
Pour point	°C	ASTM D 97	-27 max.
T. B. N.	mg KOH/g	ASTM D 2896	7,0
Bosch Injector Shearing:	cSt	CEC L-14-A-93	12,5 min.

The above-mentioned characteristics are typical values and should not be considered product specifications.

A safety information file is available on request.

repsol.com  
+34 901 111 999  
lubricantes@repsol.com

Technical data sheet for Lubricant RAS007. Revision 1. March 2020.