

REPSOL MXR MATIC PLUS



ACTION SERIES MOTORCYCLE

Lubricants

Description

High-quality semi synthetic engine oil for high performance 4T engines in Matic Scooters, which contains special additives that improve lubricity and low friction coefficient to provide JASO MB quality standard. It is recommended for use in motorcycles that require a low-friction lubricant (This formulation is recommended especially for dry-clutch scooters and automatic-transmission motorcycles).

Properties

- The trials in four-stroke motorcycles under extreme working conditions have confirmed excellent protection against wear and outstanding output due to its viscosity.
- Its formula offers a top tier performance for the most demanding engines
- Unique friction modifier additives intended for fuel savings, keeping the engine protected.

Quality levels

- API SN / SM
- JASO T 903:2016 MB

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			10W40
Density a 15 °C	g/mL	ASTM D 4052	0.821
Viscosity at 100 °C	cSt	ASTM D 445	14.45
Viscosity at 40 °C	cSt	ASTM D 445	100
Viscosity at -25 °C	cP	ASTM D 5293	7000 max.
Viscosity index	-	ASTM D 2270	160
Flash point, open cup	°C	ASTM D 92	244
Pour point	°C	ASTM D 97	-24
T.B.N.	mg KOH/g	ASTM D 2896	8.0
Sulphated ashes	% in weight	ASTM D 874	0.7
Noak Volatility	% in weight	ASTM D 5800	7.7

The above mentioned characteristics are typical values and should not be considered product specifications

A safety data sheet is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 1. March 2020.