

REPSOL RSGEAR PLATINUM EP5



ACTION SERIES TRANSMISSIONS

Lubricants

Description

Repsol RSGEAR PLATINUM EP-5 75W90 is a fully synthetic gear oil offering outstanding resistance to aging and providing long drain intervals in the most demanding applications. It has been designed to protect the axle against the wear under high temperature conditions by passenger cars, towing and off-road applications. It exceeds the requirements requested for GL-5 Specification making this lubricant suitable for most of the vehicles requesting a GL-5 75W90 viscosity. The right product to deal with the newest drivetrain designs with heavy loads and more torque

Properties

- Protects gears against moisture, preventing corrosion and increasing transmission life-span.
- It has excellent oxidation stability, even in extreme conditions, thus making the product more durable, which enables long drainage periods.
- Its excellent fluidity at low temperatures contributes to fuel saving, while providing the viscosity characteristics required for optimum lubrication.
- High anti-wear protection which enhances the durability of the mechanisms

Quality Levels

- API GL-5 / MT-1

Technical Specifications

	UNIT	METHOD	VALUE
SAE grade			75W90
Density at 15° C	g/cm ³	ASTM D 4052	0.85
Viscosity at 100° C	cSt	ASTM D 445	15
Viscosity at 40° C	cSt	ASTM D 445	73,12
Viscosity index	-	ASTM D 2270	219
Flash point, V/A	°C	ASTM D 92	190
Pour point	°C	ASTM D 97	-40

The above-mentioned characteristics are typical values and should not be considered product specifications.

A safety data sheet is available on request.

repsol.com
+34 901 111 999
lubricantes@repsol.com

Technical data sheet for Lubricant RAS300. Revision 1. March 2023.