

REPSOL MXR PLATINUM



ACTION SERIES MOTORCYCLE

Lubricants

Description

Repsol MXR Platinum is a top tier, fully synthetic lubricant oil for modern 4-stroke engines. It provides maximum protection for medium and high cylinder capacity engines with one, two, three or even four cylinders. The lubricant ensures maximum care to the engine components, while ensuring optimum clutch performance. It provides the ultimate boost, achieving immediate response from the engine.

Properties

- Multigrade oil with excellent thermal stability thanks to its fully synthetic formula.
- Thanks to its viscometric properties, it enhances the engine's cold start performance. It also provides adequate lubrication over a wider range of temperatures.
- Its high detergent-dispersant level supports engine cleaning, maintains soot in suspension, and prevents piston deposit formation.
- Provides adequate friction on clutch discs, preventing slippages and premature wear in joint engine and transmission (wet clutch) lubrication systems

Quality levels

- API SN
- JASO T 903:2016 MA2

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			10W-30
Density a 15 °C	g/mL	ASTM D 4052	0,842
Viscosity at 100 °C	cSt	ASTM D 445	11,17
Viscosity at 40 °C	cSt	ASTM D 445	68
Viscosity at -25 °C	cP	ASTM D 5293	7000 max.
Viscosity index	-	ASTM D 2270	162
Flash point, open cup	°C	ASTM D 92	230
Pour point	°C	ASTM D 97	-36
T.B.N.	mg KOH/g	ASTM D 2896	7
Sulphated ashes	% in weight	ASTM D 874	1.0
Bosch Injector Shearing: Viscosity at 100 °C after shear	cSt	CEC-L014-93	9,3 min.

The above mentioned characteristics are typical values and should not be considered product specifications.

A safety information file is available on request.

repsol.com
+34 901 111 999
lubricantes@repsol.com

Technical data sheet for Lubricant RAS204. Revision 1. March 2020.